

## **Product Code**

**8A1069**

Substrate Type	Woven fiberglass ("E" type) With Proprietary Coating	
Coated Weight	2.085 – 2.320 1131 - 1253	(pounds/sq.yd.) (grams/sq.meter)
Overall Thickness	0.0270" - 0.0300" 0.686 - 0.762	(inches) (mm)
Substrate Thickness (nominal)	0.0217" 0.551	(inches) (mm)
Operating Temperature	-100°F to +500°F -73°C to +260°C	(continuous)
Breaking Strength (minimum)	w=425 / f=500 3721 / 4378	(pounds/inch of width) (Newtons/5cm)
Tear Strength (trapezoid method) (minimum)	w=10.0 / f=8.7 4.55 / 3.96	(pounds) (kilograms)
Elongation % (minimum)	w=4.2 / f=3.4	(@ break)
Dielectric Strength (minimum)	110	(volts/mil)
Adhesion (resin to substrate) (minimum)	w=10.0 / f=11.7 87.6 / 102.5	(pounds/inch of width) (Newtons/5cm)

---

The data herein is based on controlled sample test results. The information is intended for comparison purposes only as each manufactured lot will exhibit normal variation. Users are expected to determine product suitability for their specific intended use before application. All data is subject to change without notice.