



Product Specification 7305KG

Taconic 7305KG is a 30 mil, Natural/Gold colored open mesh PTFE coated Kevlar and fiberglass fabric. This fabric comes with 1/4" square mesh openings to encourage good airflow. The mesh fabric has excellent heat resistance and good release properties. The Kevlar & Glass combination fabric offers exceptionally high tensile strength. Common applications involve conveyor belting applications where breaking strength and air flow are required. Maximum width is 118" wide.

Product Properties	Units	Value	Tolerance	Test Method
Reinforcing Substrate		ARAMID/E-GLASS		
Coating Type		PTFE		
% Coating	%	52	+/- 2%	
Total Coated Weight	lbs/yd2	1.25	+/- 5%	ASTM D4969
Nominal Thickness	inch	0.035		ASTM D4969
Tensile Strength	lbf/in	450	Typical Warp	ASTM D902
		350	Minimum Warp	
		600	Typical Fill	
		500	Minimum Fill	
Win Open Size (length)	inch	0.152		
Win Open Size (Width)	inch	0.181		
Opening Area	inch/square	0.0274		
Operating Temperature	°Farhenheit	-100° to +356°		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Taconic Headquarters
Petersburgh, NY
www.4taconic.com
info@4taconic.com

Please contact us for samples or a quotation

Western US, Mexico & Central America
La Verne, CA
www.4taconic.com
info@4taconic.com

Canada
Mississauga, CAN
www.4taconic.com
info@4taconic.com



For queries in Europe please visit www.taconic-ipd.com
or email info@taconic-ipd.com

