



Product Specification 7025-60/80-CFM

Taconic 7025 60/80 is a 2 mil porous PTFE coated fiberglass fabric with a porosity range of 50-90 CFMs. This material is referred to as a bleeder cloth. This fabric is commonly used as a release sheet in the production of composite materials. The construction of the fabric allows for release properties and “bleed through” where required. Maximum width is 61.5” wide.

Product Properties	Units	Value	Tolerance	Test Method
Reinforcing Substrate		E-GLASS		
Coating Type		PTFE		
% Coating	%	29	+/- 2%	
Total Coated Weight	lbs/yd2	0.12	+/- 5%	ASTM D4969
Nominal Thickness	inch	0.0025		ASTM D4969
Tensile Strength	lbf/in	55	Typical Warp	ASTM D902
		45	Minimum Warp	
		50	Typical Fill	
		40	Minimum Fill	
Tear Strength	lbs	4.5	Typical Warp	ASTM D5587
		3.5	Minimum Warp	
		6	Typical Fill	
		5	Minimum Fill	
Porosity	CFM	50	Nominal	ASTM D737
Operating Temperature	°Fahrenheit	-100° to +500°		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Taconic Headquarters
Petersburgh, NY
www.4taconic.com
info@4taconic.com

Please contact us for samples or a quotation

Western US, Mexico & Central America
La Verne, CA
www.4taconic.com
info@4taconic.com

Canada
Mississauga, CAN
www.4taconic.com
info@4taconic.com



For queries in Europe please visit www.taconic-ipd.com
or email info@taconic-ipd.com

