



Product Specification 6115-10

Taconic 6115-10 is a skived virgin PTFE film tape complete with silicone adhesive. This tape is highly conformable and has a very low coefficient of friction. The non-stick PTFE film surface is ideal for wear stripping, lining, and for chemical resistance. With silicone adhesive, this tape is suited for applications in elevated temperatures. This tape is available with a dimpled yellow release liner. Maximum width is 38" wide.

Product Properties	Units	Value	Tolerance	Test Method
Adhesive Type		SILICONE		
Substrate Type		PTFE FILM		
Total Weight of Substrate		N/A		
% Coating of Substrate		N/A		
Substrate Thickness	inch	0.01		ASTM D3652
Adhesive Thickness	inch	0.002		ASTM D3652
Total Product Thickness	inch	0.012		ASTM D3652
Adhesive Strength	ozs	48	Typical	ASTM D3330 METHOD A
		35	Minimum	
Adhesive Shelf Life	Months	6	from date of shipment	
Operating Temperature	°Fahrenheit	-100° to +500°		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Please contact us for samples or a quotation

Taconic Headquarters
Petersburgh, NY
www.4taconic.com
info@4taconic.com

Western US, Mexico & Central America
La Verne, CA
www.4taconic.com
info@4taconic.com

Canada
Mississauga, CAN
www.4taconic.com
info@4taconic.com



For queries in Europe please visit www.taconic-ipd.com
or email info@taconic-ipd.com

