



Product Specification **6605-07HP**

Taconic 6605-07HP is a woven fiberglass cloth tape complete with a high performance silicone adhesive. This pressure sensitive tape is rated class “H” as an insulator. This tape is as a UL approved electrical insulation tape used for small motor rewind/repair, transformer insulation, cable splicing, and light duty thermal spray masking. This tape is produced self wound (No Liner). Maximum width is 42” wide.

| Product Properties | Units | Value | Tolerance | Test Method |
|---------------------------|-------------|-----------------------|-----------|------------------------|
| Adhesive Type | | SILICONE | | |
| Substrate Type | | E-GLASS | | |
| Total Weight of Substrate | | 0.245 | | |
| % Coating of Substrate | | N/A | | |
| Substrate Thickness | inches | 0.005 | | ASTM D3652 |
| Adhesive Thickness | | 0.002 | | ASTM D3652 |
| Total Product Thickness | inches | 0.007 | | ASTM D3652 |
| Adhesive Strength | | 40 | Typical | ASTM D3330 METHOD A |
| | | 30 | Minimum | |
| Adhesive Shelf Life | Months | 12 | From DOM | |
| Operating Temperature | °Fahrenheit | -100° to +500° | | |

Storage conditions for all Tapes: Temperature -23 C +/- 4 C (66.2F~80.6F) and Relative Humidity- 50% +/- 10%

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Taconic Headquarters
Petersburgh, NY
www.4taconic.com
info@4taconic.com

Please contact us for samples or a quotation

Western US, Mexico & Central America
La Verne, CA
www.4taconic.com
info@4taconic.com

Canada
Mississauga, CAN
www.4taconic.com
info@4taconic.com



For queries in Europe please visit www.taconic-ipd.com
or email info@taconic-ipd.com

