



## Product Specification 6113-05

Taconic 6113-05 is a skived virgin PTFE film tape complete with acrylic adhesive. This tape is highly conformable and has a very low coefficient of friction. The non-stick PTFE film surface is ideal for wear stripping, lining, and for chemical resistance. This tape is available with a blue poly release liner. Maximum width is 38" wide.

Product Properties	Units	Value	Tolerance	Test Method
Adhesive Type		<b>ACRYLIC</b>		
Substrate Type		<b>PTFE FILM</b>		
Total Weight of Substrate		<b>N/A</b>		
% Coating of Substrate		<b>N/A</b>		
Substrate Thickness	inch	<b>0.005</b>		ASTM D3652
Adhesive Thickness	ozs	<b>0.002</b>		ASTM D3652
Total Product Thickness	inch	<b>0.007</b>		ASTM D3652
Adhesive Strength	oz/in	<b>70</b>	Typical	ASTM D3330 METHOD A
		<b>35</b>	Minimum	
Elongation	%	<b>300</b>		ASTM 3759
Adhesive Shelf Life	Months	<b>24</b>	From DOM	
Operating Temperature	°Fahrenheit	<b>-40° to +350°</b>		

**Storage conditions for all Tapes: Temperature -23 C +/- 4 C (66.2F~80.6F) and Relative Humidity- 50% +/- 10%**

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



**Taconic Headquarters**  
Petersburgh, NY  
[www.4taconic.com](http://www.4taconic.com)  
[info@4taconic.com](mailto:info@4taconic.com)

Please contact us for samples or a quotation

**Western US, Mexico & Central America**  
La Verne, CA  
[www.4taconic.com](http://www.4taconic.com)  
[info@4taconic.com](mailto:info@4taconic.com)

**Canada**  
Mississauga, CAN  
[www.4taconic.com](http://www.4taconic.com)  
[info@4taconic.com](mailto:info@4taconic.com)



For queries in Europe please visit [www.taconic-ipd.com](http://www.taconic-ipd.com)  
or email [info@taconic-ipd.com](mailto:info@taconic-ipd.com)



Rev: 01/23 - 004