



Product Specification 6145-02D-CLEAR

Taconic 6145-02D is a pressure sensitive tape constructed from FEP (Fluorinated Ethylene Propylene) film and is completed with a high temperature silicone adhesive. This film tape is optically clear and exhibits excellent electrical insulation properties and strong chemical resistance. This tape is available with a clear release liner. Maximum width is 24" wide.

Product Properties	Units	Value	Tolerance	Test Method
Adhesive Type		SILICONE		
Substrate Type		FEP		
Total Weight of Substrate		N/A		
% Coating of Substrate		N/A		
Substrate Thickness	inch	0.002		ASTM D3652
Adhesive Thickness	ozs	0.002		ASTM D3652
Total Product Thickness	inch	0.004		ASTM D3652
Adhesive Strength	oz/in -	30	Typical	ASTM D3330 METHOD A
		20	Minimum	
Elongation	%	300		
Adhesive Shelf Life	Months	12	From DOM	
Operating Temperature	°Fahrenheit	-100° to +400°		

Storage conditions for all Tapes: Temperature -23 C +/- 4 C (66.2F~80.6F) and Relative Humidity- 50% +/_ 10%

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Taconic Headquarters
Petersburgh, NY
www.4taconic.com
info@4taconic.com



Please contact us for samples or a quotation

Western US, Mexico & Central America

La Verne, CA

www.4taconic.com info@4taconic.com

For queries in Europe please visit www.taconic-ipd.com
or email info@taconic-ipd.com

Canada Mississauga, CAN www.4taconic.com info@4taconic.com





Rev: 07/23 - 004