



Product Specification 6603-07

Taconic 6603-07 is a woven fiberglass cloth tape complete with acrylic adhesive. This pressure sensitive tape is rated class "F" as an insulator. This tape is as an electrical insulation tape for small motor rewind applications, transformer insulation, and cable splicing. This tape is produced self wound (No Liner). Maximum width is 42" wide.

Product Properties	Units	Value	Tolerance	Test Method
Adhesive Type		ACRYLIC		
Substrate Type		E-GLASS		
Total Weight of Substrate		0.245		
% Coating of Substrate		N/A		
Substrate Thickness	inch	0.005		ASTM D3652
Adhesive Thickness	inch	0.002		ASTM D3652
Total Product Thickness	inch	0.007		ASTM D3652
Adhesive Strength	ozs	35	Typical	ASTM D3330 METHOD A
		20	Minimum	
Adhesive Shelf Life	Months	24	From DOM	
Operating Temperature	°Fahrenheit	-40° to +350°		

Storage conditions for all Tapes: Temperature -23 C +/- 4 C (66.2F~80.6F) and Relative Humidity- 50% +/- 10%

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Taconic Headquarters
Petersburgh, NY
www.4taconic.com
info@4taconic.com

Please contact us for samples or a quotation

Western US, Mexico & Central America
La Verne, CA
www.4taconic.com
info@4taconic.com

Canada
Mississauga, CAN
www.4taconic.com
info@4taconic.com



For queries in Europe please visit www.taconic-ipd.com
or email info@taconic-ipd.com

