



## Product Specification **6605-07HT**

Taconic 6605-07HT is a woven fiberglass cloth tape complete with silicone adhesive. This pressure sensitive tape is rated class “H” as an insulator. This tape is as a UL approved electrical insulation tape used for small motor rewind/repair, transformer insulation, cable splicing, and light duty thermal spray masking. This tape is produced self wound (No Liner). Maximum width is 42” wide.

Product Properties	Units	Value	Tolerance	Test Method
Adhesive Type		<b>SILICONE</b>		
Substrate Type		<b>E-GLASS</b>		
Total Weight of Substrate		<b>0.245</b>		
% Coating of Substrate		<b>N/A</b>		
Substrate Thickness	inch	<b>0.005</b>		ASTM D3652
Adhesive Thickness	inch	<b>0.002</b>		ASTM D3652
Total Product Thickness	inch	<b>0.007</b>		ASTM D3652
Adhesive Strength	ozs	<b>30</b>	Typical	ASTM D3330 METHOD A
		<b>20</b>	Minimum	
Adhesive Shelf Life	Months	<b>12</b>	From DOM	
Operating Temperature	°Fahrenheit	<b>-100° to +500°</b>		

**Storage conditions for all Tapes: Temperature -23 C +/- 4 C (66.2F~80.6F) and Relative Humidity- 50% +/- 10%**

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Please contact us for samples or a quotation

**Taconic Headquarters**  
Petersburgh, NY  
[www.4taconic.com](http://www.4taconic.com)  
[info@4taconic.com](mailto:info@4taconic.com)

**Western US, Mexico & Central America**  
La Verne, CA  
[www.4taconic.com](http://www.4taconic.com)  
[info@4taconic.com](mailto:info@4taconic.com)

**Canada**  
Mississauga, CAN  
[www.4taconic.com](http://www.4taconic.com)  
[info@4taconic.com](mailto:info@4taconic.com)



For queries in Europe please visit [www.taconic-ipd.com](http://www.taconic-ipd.com)  
or email [info@taconic-ipd.com](mailto:info@taconic-ipd.com)

