



Product Specification 6093-03

Taconic 6093-03 is a PTFE coated fiberglass tape complete with acrylic adhesive. This pressure sensitive tape has a premium weight of PTFE coating. This tape backing offers excellent release properties, chemical resistance, and a low coefficient of friction. The tape is available with a blue smooth release liner, but is also available self wound (no liner) upon request. This tape is typically used in medium temperature applications involving packaging, plastics, and roll covering where high tack and peel is beneficial. Maximum width is 42" wide.

Product Properties	Units	Value	Tolerance	Test Method
Adhesive Type		ACRYLIC		
Substrate Type		PTFE E-GLASS		
Total Weight of Substrate	lbs/yd ²	0.275		
% Coating of Substrate	%	68		
Substrate Thickness	inch	0.003		ASTM D3652
Adhesive Thickness	inch	0.002		ASTM D3652
Total Product Thickness	inch	0.005		ASTM D3652
Adhesive Strength	ozs	45	Typical	ASTM D3330 METHOD A
		35	Minimum	
Adhesive Shelf Life	Months	6	from date of shipment	
Operating Temperature	°Fahrenheit	-40° to +350°		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



#3083

Taconic Headquarters
Petersburgh, NY
www.4taconic.com
info@4taconic.com

Please contact us for samples or a quotation

Western US, Mexico & Central America
La Verne, CA
www.4taconic.com
info@4taconic.com

Canada
Mississauga, CAN
www.4taconic.com
info@4taconic.com



For queries in Europe please visit www.taconic-ipd.com
or email info@taconic-ipd.com



Rev: 01/17 - 002