



## Product Specification 7102

Taconic's 7102 is a glass fibre product coated with silicone, whose high friction and release properties offer excellent value and performance across a wide variety of industrial applications. With its abrasion and flex resistant surface, excellent chemical resistance, superior dielectric and release properties, 7102 is used as a high friction conveyor belt and electrical insulator in many industries and also as a curtain material in packaging applications. Standard width of 7102 is 1000mm, with colour availability in red or white.

Product Properties	Units	Value	Tolerance	Test Method
Reinforcing Substrate		<b>E-GLASS</b>		
Coating Type		<b>SILICONE RUBBER</b>		
% Coating	%	<b>68</b>		ISO 2286-2
Total Coated Weight	g/m <sup>2</sup>	<b>340</b>	+/- 5%	ISO 2286-2
Nominal Thickness	mm	<b>235</b>		ISO 2286-3
Tensile Strength	%	<b>900</b>	Typical Warp	ISO 1421
		<b>650</b>	Minimum Warp	
		<b>N/A</b>	Typical weft	
		<b>N/A</b>	Minimum weft	
Colour		<b>White</b>		
Rubber Hardness		<b>78</b>		
Operating Temperature	°Celsius	<b>-73° to +230°</b>		

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Please contact us for samples or a quotation

**Taconic International Ltd**  
Ireland  
[www.taconic-ipd.com](http://www.taconic-ipd.com)  
[info@taconic-ipd.com](mailto:info@taconic-ipd.com)



**Taconic France**  
France  
[www.taconic-ipd.fr](http://www.taconic-ipd.fr)  
[info@taconic-ipd.fr](mailto:info@taconic-ipd.fr)

**Taconic International Ltd**  
Germany  
[www.taconic.de](http://www.taconic.de)  
[info@taconic.de](mailto:info@taconic.de)

**Wildcat Taconic**  
United Kingdom  
[www.taconic-ipd.com](http://www.taconic-ipd.com)  
[info@wildcat-taconic.com](mailto:info@wildcat-taconic.com)



**Taconic SP z.o.o**  
Poland  
[www.taconic-ipd.pl](http://www.taconic-ipd.pl)  
[biuro@4taconic.com](mailto:biuro@4taconic.com)



For queries in North America please visit [www.4taconic.com](http://www.4taconic.com) or email [info@4taconic.com](mailto:info@4taconic.com)